



QuAD T5

Features:

High luminance output (incl control options) as alternative to HID fittings with significant energy savings. Best value multi-tube T5 fitting for warehousing and production applications.

Uses high spec refined design light reflectors to direct maximum light to the work area.

With two long life HF electronic ballasts, one lamp failure doesn't turn off the fitting.

T5 tubes are instant on/off and available in a range of colour temperatures. They can be coated for sleeved for shatter proofing.

Construction:

Galvanised body – optional painted finish

High performance Miro 5 reflector

Dim: 1350mm or 1650mm long* 420mm wide* 140mm deep (wide beam) and 200mm deep (narrow beam)

Optional clear polycarbonate cover

Range:

- QUAD120 – 4*28W, 4*54W T5
- QUAD150 – 4*35W, 4*49W, 4*80W T5

Options:

- Integrated PIR sensor with built-in photo cell with on/off control
- Integrated PIR sensor with built-in photo cell with dimming control
- Shatterproofing with FEP coating
- Sleeving for cold temperature applications
- 3hr Emergency lighting kit

Compliance to following standards:

- | | |
|----------------------------------|--------------|
| • Safety: | EN 60598 |
| • Harmonics: | EN 61000-3-2 |
| • RFI-suppression: | EN 55015 |
| | EN 55022 A |
| • Performance: | EN 60929 |
| • Immunity: | EN 61547 |
| • Control gear general & safety: | EN 61437-1 |